

Dell ACS Advanced Console Servers

- Secure remote management for serial devices
- LTE/4G cellular remote access
- FIPS 140-2 compliant cryptography
- Easy To Deploy and Maintain with Zero Touch Provisioning



| ACS Feature | ACS Benefit |
|---|--|
| Secure In-Band and Out-of-Band Network connectivity for remote access to serial devices | Provides users with the ability to access a device with a serial connection that is in a non-working state, even when the primary network is down |
| Auto-discovery tool | Easier configuration and management of console servers by detecting the host name of the connected target device and updating the configuration automatically |
| Dual Gigabit Ethernet ports and Dual AC Power | Provides hardware redundancy for improved reliability and uptime |
| Using internal modem or external cellular LTE/4G connectivity | Remote out-of-band access through the internal modem or alternately using a LTE/4G cellular network to access devices with a serial connection that are not accessible through the primary network |
| Dell-specific accessories | Simplifies connectivity to Dell equipment |



Contacts: Simone Kempmann
Key Account Manager - EMEA
simone.kempmann@emerson.com

Arnaud Tassin
Product & Business Manager
EMEA | Emerson
arnaud_tassin@dell.com

Team email:
godell-EMEA@emerson.com

Visit our customer-facing site for documents, SKUs, FAQs and other information:

www.dellkvm.com

DCI Dashboard:
<https://dell.gosavo.com/CustomPage/View.aspx?id=37256410>

Dell ACS Advanced Console Servers

UK, FR, DE, Western Countries



| | DACS6008MDAC-KT | DACS6016MDAC-KT | DACS6032MDAC-KT | DACS6048MDAC-KT |
|-----------------------------|---|-----------------|-----------------|-----------------|
| Dell Part Number | A8371799 | A8371822 | A8371801 | A8371803 |
| Device Connectors | <ul style="list-style-type: none"> • 2 Gigabit (10/100/1000BT) Ethernet interfaces • Internal modem V.92 port on RJ45 (RJ11 compatible) • 1 USB 2.0 Host on Type A connector | | | |
| RS232 ports on RJ45 | 8 | 16 | 32 | 48 |
| Management Software | <ul style="list-style-type: none"> • On-board Web Interface via browser for remote access • Compatible with Avocent DSView™ management software | | | |
| Power Supply Specifications | AC input: Dual IEC C14, 100 - 240 VAC, 50/60 Hz auto-sensing, 35W Max | | | |
| Environmental | <ul style="list-style-type: none"> • Operating: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius) • Non-operating: -4 to 158 degrees Fahrenheit (-20 to 70 degrees Celsius) | | | |

Services: Standard warranty is 3-year Advanced Replacement. Use the following SKUs to add extended warranty

| Dell P/N | Vendor Part Number | Description |
|----------|----------------------|---|
| A8371816 | DADB0036-8 | Dell RJ45 to DB9F convertor for Dell ACS6000 series console servers |
| A8618053 | 4YGLD-DACS6008MDACKT | Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6008MDACKT |
| A8618142 | 5YGLD-DACS6008MDACKT | Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6008MDACKT |
| A8618072 | 4YGLD-DACS6016MDACKT | Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6016MDACKT |
| A8618190 | 5YGLD-DACS6016MDACKT | Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6016MDACKT |
| A8618090 | 4YGLD-DACS6032MDACKT | Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6032MDACKT |
| A8618167 | 5YGLD-DACS6032MDACKT | Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6032MDACKT |
| A8618108 | 4YGLD-DACS6048MDACKT | Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6048MDACKT |
| A8618210 | 5YGLD-DACS6048MDACKT | Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6048MDACKT |