Dell ACS Advanced Console Servers

- Secure remote management for serial devices
- LTE/4G cellular remote access
- FIPS 140-2 compliant cryptography
- Easy To Deploy and Maintain with Zero Touch Provisioning



| ACS Feature | ACS Benefit | | |
|---|--|--|--|
| Secure in-Band and Out-of-Band Network connectivity for remote access to serial devices | Provides users with the ability to access a device with a serial connection that is in a non-working state, even when the primary network is down | | |
| Auto-discovery tool | Easier configuration and management of console servers by detecting the host name of the connected target device and updating the configuration automatically | | |
| Dual Gigabit Ethernet ports and Dual AC Power | Provides hardware redundancy for improved reliability and uptime | | |
| Using internal modern or external cellular LTE/4G connectivity | Remote out-of-band access through the internal modem or alternately using a LTE/4G cellular network to access devices with a serial connection that are not accessible through the primary network | | |
| Dell-specific accessories | Simplifies connectivity to Dell equipment | | |





Contacts: Chris Ruffing
Dell Alliance Manager
T: 512.934.8270
Chris Ruffing@emerson.com

Steven Grasley Dell Alliance Manager 512-534-1693 steven.grasley@emerson.com Visit our customer-facing site for documents, SKUs, FAQs and other information: www.dellkvm.com

Team email: goDell@emerson.com

Dell ACS Advanced Console Servers





| | | DACS6008MDAC-KT | | DACS6016MDAC-KT | DACS6032MDAC-KT | DACS6048MDAC-KT | | |
|---|-------------------------|--|---|---|-----------------|-----------------|--|--|
| Dell Part Numb | Dell Part Number A83717 | | '99 | A8371822 | A8371801 | A8371803 | | |
| • Internal mode | | 00/1000BT) Ethernet interfaces m V.92 port on RJ45 (RJ11 compatible) con Type A connector | | | | | | |
| RS232 ports on | orts on RJ45 8 | | | 16 | 32 | 48 | | |
| Management S | Software | On-board Web Interface via browser for remote access Compatible with Avocent® DSView™ management software | | | | | | |
| Power Supply Sp | pecifications | AC input: Dual IEC C14, 100 - 240 VAC, 50/60 Hz auto-sensing, 35W Max | | | | | | |
| Environmental | | Operating: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius) Non-operating: -4 to 158 degrees Fahrenheit (-20 to 70 degrees Celsius) | | | | | | |
| Services: Standard warranty is 3-year Advanced Replacement. Use the following SKUs to add extended warranty | | | | | | | | |
| Dell P/N | Vendor Part Number | | Description | | | | | |
| A8371816 | DADB0036-8 | | Dell RJ45 to DB9F convertor for Dell ACS6000 series console servers | | | | | |
| A8496827 | 4YGLD-DACS6008MDACKT | | Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6008MDACKT | | | | | |
| A8496837 | 5YGLD-DACS6008MDACKT | | Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6008MDACKT | | | | | |
| A8496829 | 4YGLD-DACS6016MDACKT | | Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6016MDACKT | | | | | |
| A8496841 | 5YGLD-DACS6016MDACKT | | Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6016MDACKT | | | | | |
| A8496830 | 4YGLD-DACS6032MDACKT | | Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6032MDACKT | | | | | |
| A8496843 | 5YGLD-DACS6032MDACKT | | Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6032MDACKT | | | | | |
| A8496831 | 4YGLD-DACS6048MDACKT | | Dell 4 Year | Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6048MDACKT | | | | |
| A8496844 | 5YGLD-DACS6048MDACKT | | Dell 5 Year | Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6048MDACKT | | | | |