

# Avocent® Advanced Console Server for Dell

- Secure remote management for serial devices
- LTE/4G cellular remote access
- FIPS 140-2 compliant cryptography
- Easy To Deploy and Maintain with Zero Touch Provisioning



ACS Feature	ACS Benefit
Secure In-Band and Out-of-Band Network connectivity for remote access to serial devices	Provides users with the ability to access a device with a serial connection that is in a non-working state, even when the primary network is down
Auto-discovery tool	Easier configuration and management of console servers by detecting the host name of the connected target device and updating the configuration automatically
Dual Gigabit Ethernet ports and Dual AC Power	Provides hardware redundancy for improved reliability and uptime
Using internal modem or external cellular LTE/4G connectivity	Remote out-of-band access through the internal modem or alternately using a LTE/4G cellular network to access devices with a serial connection that are not accessible through the primary network
Dell-specific accessories	Simplifies connectivity to Dell equipment



**Contacts:** Simone Kempmann  
Key Account Manager - EMEA  
simone.kempmann@emerson.com

Arnaud Tassin  
Product & Business Manager  
EMEA | Emerson  
arnaud\_tassin@dell.com

**Team email:**  
godell-EMEA@emerson.com

Visit our customer-facing site for documents, SKUs, FAQs and other information:  
[www.dellkvm.com](http://www.dellkvm.com)

# Avocent® Advanced Console Server for DELL

UK, FR, DE, Western Countries



	DACS6008MDAC	DACS6016MDAC	DACS6032MDAC	DACS6048MDAC
Dell Part Number	A8371799	A8371822	A8371801	A8371803
Device Connectors	<ul style="list-style-type: none"> <li>• 2 Gigabit (10/100/1000BT) Ethernet interfaces</li> <li>• Internal modem V.92 port on RJ45 (RJ11 compatible)</li> <li>• 1 USB 2.0 Host on Type A connector</li> </ul>			
RS232 ports on RJ45	8	16	32	48
Management Software	<ul style="list-style-type: none"> <li>• On-board Web Interface via browser for remote access</li> <li>• Compatible with Avocent DSView™ management software</li> </ul>			
Power Supply Specifications	AC input: Dual IEC C14, 100 - 240 VAC, 50/60 Hz auto-sensing, 35W Max			
Environmental	<ul style="list-style-type: none"> <li>• Operating: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius)</li> <li>• Non-operating: -4 to 158 degrees Fahrenheit (-20 to 70 degrees Celsius)</li> </ul>			

Dell P/N	Vendor Part Number	Description
A8371816	DADB0036-8	Dell RJ45 to DB9F convertor for Dell ACS6000 series console servers
Services: Standard warranty includes 8x5 phone support. Use the following SKUs to add extended warranty:		
A8618053	4YGLD-DACS6008MDAC	Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6008MDACKT
A8618142	5YGLD-DACS6008MDAC	Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6008MDACKT
A8618072	4YGLD-DACS6016MDAC	Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6016MDACKT
A8618190	5YGLD-DACS6016MDAC	Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6016MDACKT
A8618090	4YGLD-DACS6032MDAC	Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6032MDACKT
A8618167	5YGLD-DACS6032MDAC	Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6032MDACKT
A8618108	4YGLD-DACS6048MDAC	Dell 4 Year Gold Hardware Maintenance by Avocent - DACS6048MDACKT
A8618210	5YGLD-DACS6048MDAC	Dell 5 Year Gold Hardware Maintenance by Avocent - DACS6048MDACKT